

Dynacom NHQ536IR

5MP 36x Network Speed Dome Camera

- 1/2.8"SONY Starvis Back-illuminated CMOS sensor
- 36X Optical Zoom, 4.6 ~ 165mm
- 5MP(2592×1944)
- Multiple Streams H.264/H.265
- Day&Night Mode, IR cut filter
- IR Range 200m
- Auto/Manual Focus control
- Outdoor IP66



CAMERA	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Scanning Mode	Progressive Scan
Image Resolution	5MP (2592*1944)
Electronic Shutter	Auto/Manual, 1/3~ 1/100,000s
Compression	H.264/H.265
Min. Illumination	Color: 0.008 Lux @ (F1.6 AGC ON), B/W: 0.00 Lux @ (IR LED ON)
Wide Dynamic Range (WDR)	Supports, 120dB
Digital Noise Reduction	Supports
Antifog	Supports
Privacy Masking	Supports
S/N Ratio	>60db
PTZ	
Horizontal Rotation Speed	200°/s
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max.20 points
LENS	
Focus Length	4.6mm-165mm F1.6-F4.3
Focus Control	36X Optical Zoom, 12X Digital Zoom
NIGHT VISION	
Infrared LED	Φ 35x6PCS IR LEDS + 2PCS Laser LED
IR Range	200m
Day-night mode	AUTO
NETWORK	
Network protocol	TCP/IP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, ICMP, NTP, SMTP, ONVIF
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Stream type	Main Stream : 5MP(2592*1944)@20fps, 4MP(2560*1440)@25fps, 1080P(1920*1080)@30fps, 720P(1280*720)@30fps
	Sub Stream : D1(720*480)@20fps, CIF(352*288)@20fps
Streaming Method	Unicast, Multicast
GENERAL	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/4A 48W - PoE Optional
Lightning Protection	Transient voltage 6000V
Dimension	310x310x440(mm)
Weight	2.29Kgs